

Varianttabell			
E-nummer	Ytbehandling (utöver varmförzinkning)	Kulör	Glanstal
7780790	Rotlackerad	-	-

The technical drawing shows a vertical pole with a total height of 12000 mm. Key dimensions include a top arm length of 2000 mm at a 95° angle, a main shaft diameter of Ø 60,3 at the top, Ø 101,6 in the middle, and Ø 127 further down. There are three sections of 3000 mm each. Near the base, there's a section of 5150 mm with a diameter of Ø 152,4, followed by a 1200 mm section ending at ground level ('Marknivå'). A 400x100 mm access opening ('Lucköppning') is located near the bottom. A detail view 'DETAIL A' shows a cross-section with four Ø 13 holes at 90° intervals.

Topparm dold i denna vy

DETAIL A
SCALE 1 : 3

4x Ø 13 med 90° delning

Övriga anvisningar

- Tillverkad enligt: SS-EN 40
- Varmförzinkad enligt: SS-EN 1461
- Där annat inte anges gäller generell tolerans.
- Skarpa kanter brutna
- Övrig dokumentation
 - I0006 - Upphängningshål stolpar

This drawing and all oppurtenant matter shall remain the company Mora Mast AB property. They shall not without our written permission, either in their original state or with any changes be copied or manifolded shown to or in any other way communicated to or handed over to any part.

Material:	Generell tolerans: SS-EN 40	Ritad av: TH	Datum: 2013-02-22	Skala: 1:55
Benämning: MMSH120 E20		Godk. av: BÅ	Godk./Datum: 2025-04-15	Format: A3
Ritningsnr: 7780740	Vikt: 162.74 kg	Rev: D	Status: Released	Blad: 1/1